

P/N NAS1330C06K201

Description

Thread Size: 1/8", Nut Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1330C06K201

Minimum Qty (MOQ): 15 EA

NSN: 5310-01-081-5456

Schedule B: 7318.16.0085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1330C06K201 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.323 Inches Nominal
Key Length:	0.054 Inches Minimum And 0.059 Inches Maximum
Head Height:	0.063 Inches Maximum
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.185 Inches Minimum And 0.189 Inches Maximum
Nut Length:	0.547 Inches Minimum And 0.577 Inches Maximum
Err Default:	+0.161/+0.201 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.138 Inches
Head Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 430 Overall
Material Document And Classification:	Qq-w-423,form 1 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,ty 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1330 Professional/industrial Association Standard

How to Order

Order this rivnut from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/NAS1330C06K201 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.