

Description

Thread Size: 5/32", Nut Length: 1/2", rivnut

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS27130-CR94](#) [MS27130CR94](#) [AESS8-161](#)

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | NAS1330C08161 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5310-00-408-3195 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1330C08-161 Specifications

| | |
|-------------------------------------------------------|------------------------------------------------------------|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.355 Inches Nominal |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.217 Inches Minimum And 0.221 Inches Maximum |
| Nut Length: | 0.485 Inches Minimum And 0.515 Inches Maximum |
| Err Default: | +0.106/+0.161 Inches |
| Unable To Decode: | +0.106 To 0.161 Inches |
| Shank End Type: | Open |
| Thread Series: | Unc |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.164 Inches |
| Head Countersink Angle: | 99.00 Degrees Minimum And 101.00 Degrees Maximum |
| Material: | Steel Comp 430 Overall |
| Material Document And Classification: | Qq-w-423,form 1 Fed Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35,ty 2 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1330 Professional/industrial Association Standard |

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330C08-161> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.