

Description

Thread Size: 5/32", Nut Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1330C08241
Minimum Qty (MOQ):	15 EA
NSN:	5310-00-058-1806
National Motor Freight:	077140, Fruits Dried / Evaporated Noi

NO IMAGE
AVAILABLE

P/N NAS1330C08-241 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk
Head Diameter:	0.355 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.217 Inches Minimum And 0.221 Inches Maximum
Nut Length:	0.610 Inches Minimum And 0.640 Inches Maximum
Err Default:	+0.201/+0.241 Inches
Unable To Decode:	+0.201 To 0.241 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Head Countersink Angle:	100.00 Degrees Nominal
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Qq-w-423 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Specification/standard Data:	80205-nas1330 Professional/industrial Association Standard

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1330C08-241> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.