

**Description**

Thread Size: 5/32", Nut Length: 9/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                   |
|-------------------------|-------------------|
| SKU / Model:            | NAS1330C08K201    |
| Minimum Qty (MOQ):      | 10 EA             |
| NSN:                    | 5310-00-905-8426  |
| National Motor Freight: | 013540, Alum Nuts |

NO IMAGE  
AVAILABLE

## P/N NAS1330C08K201 Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                         | 3b  |
| <b>Thread Direction:</b>                     | Right-hand  |
| <b>Head Style:</b>                           | Flat Countersunk Reverse Keyed                            |
| <b>Head Diameter:</b>                        | 0.355 Inches Nominal                                      |
| <b>Key Length:</b>                           | 0.059 Inches Nominal                                      |
| <b>Head Height:</b>                          | 0.063 Inches Nominal                                      |
| <b>Nut Style:</b>                            | Blind Rivet W/smooth Round Shank                          |
| <b>Nut Diameter:</b>                         | 0.217 Inches Minimum And 0.221 Inches Maximum             |
| <b>Nut Length:</b>                           | 0.547 Inches Minimum And 0.577 Inches Maximum             |
| <b>Err Default:</b>                          | +0.161/+0.201 Inches                                      |
| <b>Shank End Type:</b>                       | Open  |
| <b>Thread Series:</b>                        | Unc   |
| <b>Thread Quantity Per Inch:</b>             | 32  |
| <b>Nominal Thread Size:</b>                  | 0.164 Inches  |
| <b>Head Countersink Angle:</b>               | 99.00 Degrees Minimum And 101.00 Degrees Maximum          |
| <b>Material:</b>                             | Steel Comp 430 Overall                                    |
| <b>Material Document And Classification:</b> | Qq-w-423,form 1 Fed Spec Single Material Response Overall |
| <b>Surface Treatment:</b>                    | Passivate Overall   |

## How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1330C08K201> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.