

P/N NAS1330C3-166

Description

NAS1330C3-166 Plain Blind Rivet Nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1330C3166

Minimum Qty (MOQ): 10

NSN: 5310-01-123-4618

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1330C3-166 Specifications

| Thread Class: | 3b |
|--|--|
| Thread Direction: | Right-hand |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.391 Inches Nominal |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.246 Inches Minimum And 0.250 Inches Maximum |
| Nut Length: | 0.610 Inches Minimum And 0.640 Inches Maximum |
| Err Default: | +0.116/+0.166 Inches |
| Shank End Type: | Open |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Head Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Steel Comp 430 Overall |
| Material Document And Classification: | 66 Fed Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |

How to Order

Order this plain blind rivet nut from our inventory online by visiting https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330C3-166 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330C3-166 and selecting the