

## P/N NAS1330C3K116

### **Description**

Thread Size: 3/16", Nut Length: 37/64", rivnut, NAS1330 series nut

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1330C3K116

Minimum Qty (MOQ): 20

NSN: 5310-00-922-6315

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1330C3K116 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.391 Inches Nominal
Key Length:	0.065 Inches Nominal
Head Height:	0.065 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.246 Inches Minimum And 0.250 Inches Maximum
Nut Length:	0.563 Inches Minimum And 0.593 Inches Maximum
Err Default:	+0.065/+0.116 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Head Countersink Angle:	100.00 Degrees Nominal
Material:	Steel Comp 430 Overall
Material Document And Classification:	Qq-w-423,form 1 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall

## **How to Order**

Order this plain blind rivet nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330C3K116">https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330C3K116</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330C3K116">https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330C3K116</a> and selecting the