

Description

Thread Size: 3/16", Nut Length: 53/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------------------------|
| SKU / Model: | NAS1330C3KB116 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5310-00-068-0221 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 077140, Fruits Dried / Evaporated Noi |

NO IMAGE
AVAILABLE

P/N NAS1330C3KB116 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Head Style: | Flat Countersunk Reverse Keyed |
| Head Diameter: | 0.391 Inches Nominal |
| Key Length: | 0.065 Inches Maximum |
| Head Height: | 0.065 Inches Maximum |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.246 Inches Minimum And 0.250 Inches Maximum |
| Nut Length: | 0.828 Inches Nominal |
| Err Default: | +0.065/+0.116 Inches |
| Unable To Decode: | +0.065 To 0.116 Inches |
| Shank End Type: | Closed |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Head Countersink Angle: | 100.00 Degrees Nominal |
| Material: | Steel Comp 430 Overall |
| Material Document And Classification: | Qq-w-423,form 1 Fed Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35,ty 2 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1330 Professional/industrial Association Standard |

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1330C3KB116> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.