

P/N NAS1330C3KB116

Description

Thread Size: 3/16", Nut Length: 53/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1330C3KB116

Minimum Qty (MOQ): 10

NSN: 5310-00-068-0221

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 077140, Fruits Dried / Evaporated Noi



^{*} See page 2 for technical characteristics

P/N NAS1330C3KB116 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.391 Inches Nominal
Key Length:	0.065 Inches Maximum
Head Height:	0.065 Inches Maximum
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.246 Inches Minimum And 0.250 Inches Maximum
Nut Length:	0.828 Inches Nominal
Err Default:	+0.065/+0.116 Inches
Unable To Decode:	+0.065 To 0.116 Inches
Shank End Type:	Closed
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Head Countersink Angle:	100.00 Degrees Nominal
Material:	Steel Comp 430 Overall
Material Document And Classification:	Qq-w-423,form 1 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,ty 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1330 Professional/industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/NAS1330C3KB116 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.