

Description

Thread Size: 3/16", Nut Length: 31/32", rivnut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1330C3KB316
Minimum Qty (MOQ):	20
NSN:	5310-00-567-5304
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



P/N NAS1330C3KB316 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.391 Inches Minimum
Key Length:	0.065 Inches Maximum
Head Height:	0.065 Inches Maximum
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.246 Inches Minimum And 0.250 Inches Maximum
Nut Length:	0.951 Inches Minimum And 0.981 Inches Maximum
Err Default:	+0.266/+0.316 Inches
Unable To Decode:	+0.266 To 0.316 Inches
Shank End Type:	Closed
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Head Countersink Angle:	100.00 Degrees Nominal
Material:	Steel Comp 430 Overall
Material Document And Classification:	Qq-w-423,form 1 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,ty 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1330 Professional/industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330C3KB316> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.