

Description

Rivnut part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1330C4EK271 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-01-524-8811 |
| Schedule B: | 7318.16.0085 |
| ECCN: | 9A991 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



* See page 2 for technical characteristics

P/N NAS1330C4EK271 Specifications

| | |
|--|--|
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.332 Inches Nominal |
| Head Major Diameter: | 0.529 Inches Nominal |
| End Item Identification: | Nsn: 2350-01-368-9500 |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 28 |
| Nominal Thread Size: | 0.2500 Inches |
| Countersink Angle: | 100.0 Degrees Nominal |
| Head Countersink Angle: | 100.0 Degrees Nominal |
| Part Name Assigned By Controlling Agency: | Nut, Blind Rivet - Countersunk Head, Internal Thd, Non-locking (free Running) And Self-locking (prevailing Torque) |
| Material: | Steel Overall |
| Special Test Features: | Install Hole Size: .332 Min And .338 Max |

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1330C4EK271> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.