

Description

Thread Size: 1/4", Nut Length: 11/16", NAS1330 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS27130-CR105K](#) [AESS2528K151](#) [SS2528K151](#)

SKU / Model:	NAS1330C4K151
Minimum Qty (MOQ):	10
NSN:	5310-00-930-0671
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1330C4K151 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.529 Inches Nominal
Key Length:	0.089 Inches Nominal
Head Height:	0.089 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.328 Inches Minimum And 0.332 Inches Maximum
Nut Length:	0.672 Inches Minimum And 0.702 Inches Maximum
Err Default:	+0.089/+0.151 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Head Countersink Angle:	100.00 Degrees Nominal
Material:	Steel Comp 430 Overall
Material Document And Classification:	Qq-w-423,form 1 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1330C4K151> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.