

Description

Thread Size: 5/16-24, Nut Length: 55/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1330C5K181
Minimum Qty (MOQ):	5
NSN:	5310-01-038-2289
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1330C5K181 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.656 Inches Nominal
Key Length:	0.104 Inches Maximum
Head Height:	0.104 Inches Maximum
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.409 Inches Minimum And 0.413 Inches Maximum
Nut Length:	0.829 Inches Minimum And 0.859 Inches Maximum
Err Default:	+0.106/+0.181 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.312 Inches
Head Countersink Angle:	99.00 Degrees Minimum And 101.00 Degrees Maximum
Material:	Steel Comp 430 Overall
Material Document And Classification:	Qq-w-423,form 1 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,ty 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1330 Professional/industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330C5K181> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.