

Description

Thread Size: 3/8", Nut Length: 1-1/32

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1330C6EK296
Minimum Qty (MOQ):	5
NSN:	5310-01-509-3945
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1330C6EK296 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.770 Inches Nominal
Key Length:	0.124 Inches Maximum
Head Height:	0.124 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.486 Inches Minimum And 0.490 Inches Maximum
Nut Length:	1.016 Inches Minimum And 1.046 Inches Maximum
Err Default:	+0.211/+0.296 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	16
Nominal Thread Size:	0.375 Inches
Head Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 430 Overall
Material Document And Classification:	Fed Std 66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330C6EK296> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.