

Description

Thread Size: 4-", Nut Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1330H04K81L
Minimum Qty (MOQ):	10
NSN:	5310-00-625-8298
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1330H04K81L Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.263 Inches Nominal
Key Length:	0.051 Inches Maximum
Head Height:	0.051 Inches Maximum
Locking Feature:	Prevailing Torque All Metal Design
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.151 Inches Minimum And 0.155 Inches Maximum
Nut Length:	0.355 Inches Minimum And 0.385 Inches Maximum
Nut Grip Range:	+0.050/+0.081 Inches
Unable To Decode:	+0.050 To 0.081 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	40
Nominal Thread Size:	4.000 Inches
Head Countersink Angle:	99.00 Degrees Minimum And 101.00 Degrees Maximum
Material:	Steel Comp 4037 Overall
Material Document And Classification:	Astm A547 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1330 Professional/industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330H04K81L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.