

**Description**

Thread Size: 1/8", Nut Length: 1/2

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1330H06K161L                           |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5310-00-046-7850                          |
| Schedule B:             | 7318.16.0085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1330H06K161L Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3b  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Head Style:</b>                                    | Flat Countersunk Reverse Keyed                                |
| <b>Head Diameter:</b>                                 | 0.323 Inches Nominal  |
| <b>Key Length:</b>                                    | 0.063 Inches Maximum  |
| <b>Head Height:</b>                                   | 0.063 Inches Maximum  |
| <b>Locking Feature:</b>                               | Prevailing Torque All Metal Design                            |
| <b>Nut Style:</b>                                     | Blind Rivet W/smooth Round Shank                              |
| <b>Nut Diameter:</b>                                  | 0.185 Inches Minimum And 0.189 Inches Maximum                 |
| <b>Nut Length:</b>                                    | 0.485 Inches Minimum And 0.515 Inches Maximum                 |
| <b>Nut Grip Range:</b>                                | +0.106/+0.161 Inches  |
| <b>Unable To Decode:</b>                              | +0.106 To 0.161 Inches  |
| <b>Shank End Type:</b>                                | Open  |
| <b>Thread Series:</b>                                 | Unc   |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Nominal Thread Size:</b>                           | 0.138 Inches  |
| <b>Head Countersink Angle:</b>                        | 99.00 Degrees Minimum And 101.00 Degrees Maximum              |
| <b>Material:</b>                                      | Steel Comp 4037 Overall                                       |
| <b>Material Document And Classification:</b>          | Astm A547 Assn Std Single Material Response Overall           |
| <b>Surface Treatment:</b>                             | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| <b>Specification/standard Data:</b>                   | 80205-nas1330 Professional/industrial Association Standard    |

## How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330H06K161L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.