

Description

Thread Size: 3/16", Nut Length: 25/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1330H3K316L
Minimum Qty (MOQ):	10 EA
NSN:	5310-01-231-0690
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1330H3K316L Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.391 Inches Nominal
Key Length:	0.065 Inches Maximum
Head Height:	0.065 Inches Maximum
Locking Feature:	Prevailing Torque All Metal Design
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.246 Inches Minimum And 0.250 Inches Maximum
Nut Length:	0.766 Inches Minimum And 0.796 Inches Maximum
Err Default:	+0.266 To 0.316 Inches
Shank End Type:	Open
Temp Rating:	Not Rated
Thread Series:	Unf
Thread Quantity Per Inch:	32
Hardness Rating:	Not Rated
Nominal Thread Size:	0.190 Inches
Head Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4037 Overall
Material Document And Classification:	Astm A547 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1330 Professional/Industrial Association Standard

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1330H3K316L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.