

P/N NAS1330H4K271L

Description

Thread Size: 1/4", Nut Length: 13/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1330H4K271L

Minimum Qty (MOQ): 10

NSN: 5310-01-164-5599

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS1330H4K271L Specifications

| Thread Class: | 3b |
|--|---|
| Thread Direction: | Right-hand |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.529 Inches Nominal |
| Locking Feature: | Prevailing Torque All Metal Design |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.328 Inches Minimum And 0.332 Inches Maximum |
| Nut Length: | 0.797 Inches Minimum And 0.827 Inches Maximum |
| Nut Grip Range: | +0.211/+0.271 Inches |
| Shank End Type: | Open |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 28 |
| Nominal Thread Size: | 0.250 Inches |
| Head Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Steel Comp 4037 Overall |
| Material Document And Classification: | Qq-w-405 Fed Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1330 Professional/industrial Association Standard |

How to Order

Order this plain blind rivet nut from our inventory online by visiting https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330H4K271 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.