

**Description**

Thread Size: 1/4", Nut Length: 1-1/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1330H4KB271
Minimum Qty (MOQ):	1 EA
NSN:	5310-01-607-0190
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1330H4KB271 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat Countersunk Reverse Keyed
<b>Head Diameter:</b>	0.529 Inches Nominal
<b>Key Length:</b>	0.089 Inches Maximum
<b>Head Height:</b>	0.089 Inches Maximum
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.328 Inches Minimum And 0.332 Inches Maximum
<b>Nut Length:</b>	1.110 Inches Minimum And 1.140 Inches Maximum
<b>Err Default:</b>	-0.211 To 0.271 Inches
<b>Shank End Type:</b>	Closed
<b>Temp Rating:</b>	250.0 Deg Fahrenheit Maximum
<b>Thread Series:</b>	Unf
<b>Thread Quantity Per Inch:</b>	28
<b>Hardness Rating:</b>	20.0 Rockwell C Minimum
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Head Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Nut,blind Rivet - C'sunk Head,internal Thd,non-locking
<b>Special Features:</b>	Ultimate Thread Strength At 6590 Lbs Min
<b>Material:</b>	Steel Comp 4037 Overall
<b>Material Document And Classification:</b>	Astm A752,uns G40370 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35,ty li Fed Spec Single Treatment Response Overall

## How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1330H4KB271> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.