

Description

Thread Size: 1/4", Nut Length: 1-1/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1330H4KB271
Minimum Qty (MOQ):	1 EA
NSN:	5310-01-607-0190
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1330H4KB271 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.529 Inches Nominal
Key Length:	0.089 Inches Maximum
Head Height:	0.089 Inches Maximum
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.328 Inches Minimum And 0.332 Inches Maximum
Nut Length:	1.110 Inches Minimum And 1.140 Inches Maximum
Err Default:	-0.211 To 0.271 Inches
Shank End Type:	Closed
Temp Rating:	250.0 Deg Fahrenheit Maximum
Thread Series:	Unf
Thread Quantity Per Inch:	28
Hardness Rating:	20.0 Rockwell C Minimum
Nominal Thread Size:	0.250 Inches
Head Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Nut,blind Rivet - C'sunk Head,internal Thd,non-locking
Special Features:	Ultimate Thread Strength At 6590 Lbs Min
Material:	Steel Comp 4037 Overall
Material Document And Classification:	Astm A752,uns G40370 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-35,ty li Fed Spec Single Treatment Response Overall

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1330H4KB271> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.