

## Description

Thread Size: 1/4", Nut Length: 1-1/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1330H4KB271                            |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5310-01-607-0190                          |
| Schedule B:             | 7318.16.0085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS1330H4KB271 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3b   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Head Style:</b>                                    | Flat Countersunk Reverse Keyed                                 |
| <b>Head Diameter:</b>                                 | 0.529 Inches Nominal   |
| <b>Key Length:</b>                                    | 0.089 Inches Maximum   |
| <b>Head Height:</b>                                   | 0.089 Inches Maximum   |
| <b>Nut Style:</b>                                     | Blind Rivet W/smooth Round Shank                               |
| <b>Nut Diameter:</b>                                  | 0.328 Inches Minimum And 0.332 Inches Maximum                  |
| <b>Nut Length:</b>                                    | 1.110 Inches Minimum And 1.140 Inches Maximum                  |
| <b>Err Default:</b>                                   | -0.211 To 0.271 Inches   |
| <b>Shank End Type:</b>                                | Closed   |
| <b>Temp Rating:</b>                                   | 250.0 Deg Fahrenheit Maximum                                   |
| <b>Thread Series:</b>                                 | Unf  |
| <b>Thread Quantity Per Inch:</b>                      | 28   |
| <b>Hardness Rating:</b>                               | 20.0 Rockwell C Minimum  |
| <b>Nominal Thread Size:</b>                           | 0.250 Inches   |
| <b>Head Countersink Angle:</b>                        | 99.0 Degrees Minimum And 101.0 Degrees Maximum                 |
| <b>Part Name Assigned By Controlling Agency:</b>      | Nut,blind Rivet - C'sunk Head,internal Thd,non-locking         |
| <b>Special Features:</b>                              | Ultimate Thread Strength At 6590 Lbs Min                       |
| <b>Material:</b>                                      | Steel Comp 4037 Overall  |
| <b>Material Document And Classification:</b>          | Astm A752,uns G40370 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35,ty Ii Fed Spec Single Treatment Response Overall       |

## How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1330H4KB271> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.