

P/N NAS1330S06K201

Description

Thread Size: 1/8", Nut Length: 9/16

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS1330S06K201

Minimum Qty (MOQ): 25

NSN: 5310-00-127-3627

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1330S06K201 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.323 Inches Nominal
Key Length:	0.063 Inches Maximum
Head Height:	0.063 Inches Maximum
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.185 Inches Minimum And 0.189 Inches Maximum
Nut Length:	0.547 Inches Minimum And 0.577 Inches Maximum
Err Default:	+0.161/+0.201 Inches
Unable To Decode:	+0.161 To 0.201 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.138 Inches
Head Countersink Angle:	100.00 Degrees Nominal
Material:	Steel Comp 1108 Overall Or Steel Comp 1110 Overall
Material Document And Classification:	Qq-w-405 Fed Spec All Material Responses Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1330 Professional/industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330S06K201 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330S06K201 and selecting the