

Description

Thread Size: 5/32", Nut Length: 9/16", Rivnut, NAS1330 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1330S08K201 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5310-00-177-7662 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1330S08K201 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Head Style: | Flat Countersunk Reverse Keyed |
| Head Diameter: | 0.355 Inches Nominal |
| Key Length: | 0.063 Inches Maximum |
| Head Height: | 0.063 Inches Maximum |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.217 Inches Minimum And 0.221 Inches Maximum |
| Nut Length: | 0.547 Inches Minimum And 0.577 Inches Maximum |
| Err Default: | +0.161/+0.201 Inches |
| Unable To Decode: | +0.161 To 0.201 Inches |
| Shank End Type: | Open |
| Thread Series: | Unc |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.164 Inches |
| Head Countersink Angle: | 99.00 Degrees Minimum And 101.00 Degrees Maximum |
| Material: | Steel Comp 1108 Overall Or Steel Comp 1110 Overall |
| Material Document And Classification: | Qq-w-405 Fed Spec All Material Responses Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1330 Professional/industrial Association Standard |

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330S08K201> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.