

Description

Thread: 8-32, Thread Size: 1/8", Nut Length: 5/8", rivnut

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS27130-S96K S8-K-241](#)

SKU / Model:	NAS1330S08K241
Minimum Qty (MOQ):	25
NSN:	5310-01-281-7818
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1330S08K241 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.355 Inches Nominal
Key Length:	0.063 Inches Maximum
Head Height:	0.063 Inches Maximum
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.217 Inches Minimum And 0.221 Inches Maximum
Nut Length:	0.610 Inches Minimum And 0.640 Inches Maximum
Err Default:	+0.201/+0.241 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Head Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 1008 Overall Or Steel Comp 1010 Overall Or Steel Comp 1108 Overall Or Steel Comp 1110 Overall Or Steel Comp 1215 Overall
Material Document And Classification:	Astm A549 Assn Std 1st Material Response Overall Or Astm A576 Assn Std 2nd Material Response Overall Or Astm A108 Assn Std 3rd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1330 Professional/industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330S08K241> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.