

Description

Thread Size: 1/4", Nut Length: 5/8", Rivnut, NAS1330 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[AES10-116CSI](#)
[MS27130S99](#)
[MS27130-S99](#)

SKU / Model:	NAS1330S3116
Minimum Qty (MOQ):	25
NSN:	5310-00-999-4016
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	077140, Fruits Dried / Evaporated Noi



* See page 2 for technical characteristics

P/N NAS1330S3-116 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk
Head Diameter:	0.391 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.246 Inches Minimum And 0.250 Inches Maximum
Nut Length:	0.563 Inches Minimum And 0.593 Inches Maximum
Err Default:	+0.065/+0.116 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Head Countersink Angle:	99.00 Degrees Minimum And 101.00 Degrees Maximum
Material:	Steel Comp 1108 Overall
Material Document And Classification:	Qq-s-633-canc Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1330 Professional/industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330S3-116> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.