

Description

Thread Size: 3/16", Nut Length: 61/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | NAS1330S3B216 |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5310-00-177-7674 |
| Schedule B: | 7318.16.0085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1330S3B216 Specifications

| | |
|-------------------------------------------------------|---------------------------------------------------------------|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.391 Inches Nominal |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.246 Inches Minimum And 0.250 Inches Maximum |
| Nut Length: | 0.923 Inches Minimum And 0.953 Inches Maximum |
| Err Default: | +0.166/+0.216 Inches |
| Unable To Decode: | +0.166 To 0.216 Inches |
| Shank End Type: | Closed |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Head Countersink Angle: | 99.00 Degrees Minimum And 101.00 Degrees Maximum |
| Material: | Steel Comp 1108 Overall Or Steel Comp 1110 Overall |
| Material Document And Classification: | Qq-w-405 Fed Spec All Material Responses Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1330 Professional/Industrial Association Standard |

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1330S3B216> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.