



★ FASTENERS

Military-Fasteners.com

P/N NAS1330S3K216

Description

Thread Size: 3/16", Nut Length: 5/8", rivnut, NAS1330 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1330S3K216
Minimum Qty (MOQ):	100
NSN:	5310-00-914-3290
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1330S3K216 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.391 Inches Nominal
Key Length:	0.065 Inches Nominal
Head Height:	0.065 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.246 Inches Minimum And 0.250 Inches Maximum
Nut Length:	0.687 Inches Nominal
Err Default:	+0.166/+0.216 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Head Countersink Angle:	100.00 Degrees Nominal
Material:	Steel Comp 1108 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Specification/standard Data:	80205-nas1330 Professional/Industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330S3K216> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.