

Description

Thread Size: 3/16", Nut Length: 7/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1330S3KB166
Minimum Qty (MOQ):	20
NSN:	5310-00-890-3418
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1330S3KB166 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.391 Inches Nominal
Key Length:	0.065 Inches Maximum
Head Height:	0.065 Inches Maximum
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.246 Inches Minimum And 0.250 Inches Maximum
Nut Length:	0.860 Inches Minimum And 0.890 Inches Maximum
Err Default:	+0.116/+0.166 Inches
Shank End Type:	Closed
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Head Countersink Angle:	99.00 Degrees Minimum And 101.00 Degrees Maximum
Material:	Steel Comp 1108 Overall Or Steel Comp 1110 Overall
Material Document And Classification:	Qq-w-405 Fed Spec All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1330 Professional/Industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330S3KB166> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.