

**Description**

Thread Size: 3/8", Nut Length: 15/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1330S6K211
Minimum Qty (MOQ):	50
NSN:	5310-00-105-4122
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	077140, Fruits Dried / Evaporated Noi



\* See page 2 for technical characteristics

## P/N NAS1330S6K211 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat Countersunk Reverse Keyed
<b>Head Diameter:</b>	0.770 Inches Nominal
<b>Key Length:</b>	0.124 Inches Maximum
<b>Head Height:</b>	0.124 Inches Maximum
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.486 Inches Minimum And 0.490 Inches Maximum
<b>Nut Length:</b>	0.938 Inches Nominal
<b>Err Default:</b>	+0.125/+0.211 Inches
<b>Unable To Decode:</b>	+0.125 To 0.211 Inches
<b>Shank End Type:</b>	Open
<b>Thread Series:</b>	Unf
<b>Thread Quantity Per Inch:</b>	24
<b>Nominal Thread Size:</b>	0.375 Inches
<b>Head Countersink Angle:</b>	100.00 Degrees Nominal
<b>Material:</b>	Steel Comp 1108 Overall Or Steel Comp 1110 Overall
<b>Material Document And Classification:</b>	Aisi Assn Std All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1330 Professional/industrial Association Standard

## How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330S6K211> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.