

Description

NAS1333A3S10 Quick Release Pin

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | NAS1333A3S10 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5315-01-548-8213 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS1333A3S10 Specifications

| | |
|--|--|
| Shank Diameter: | 0.187 Inches Minimum And 0.188 Inches Maximum |
| Button Handle Diameter: | 1.200 Inches Maximum |
| Detent Quantity: | 2 |
| Actuation Method: | Push Button |
| Grip Length: | 1.000 Inches Nominal |
| Actuation Type: | Push |
| Shear Strength: | 4600 Double Pound |
| Shoulder To Head End Distance: | 1.580 Inches Maximum |
| Pin Attachment Type: | Link |
| Detent To Tapered End Distance: | 0.380 Inches Maximum |
| Material: | Aluminum Alloy 380.0 Head And Aluminum Alloy 2011 Head And Aluminum Alloy 2017 Head And Aluminum Alloy 2024 Head And Aluminum Alloy 6061 Head And Aluminum Alloy 7075 Head |
| Material: | Steel Shank |
| Material Document And Classification: | Ams-qq-a-225/3 Assn Std 1st Material Response Head And Ams-qq-a-225/5 Assn Std 2nd Material Response Head And Ams-qq-a-225/6 Assn Std 3rd Material Response Head And Ams-qq-a-200/5 Assn Std 4th Material Response Head And Ams-qq-a-225/9 Assn Std 5th Material Response Head |
| Style Designator: | Button |

How to Order

Order this quick release pin from our inventory online by visiting <https://military-fasteners.com/pins/quick+release+pins/NAS1333A3S10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.