

Description

NAS1333A3S10 Quick Release Pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1333A3S10
Minimum Qty (MOQ):	2
NSN:	5315-01-548-8213
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS1333A3S10 Specifications

Shank Diameter:	0.187 Inches Minimum And 0.188 Inches Maximum
Button Handle Diameter:	1.200 Inches Maximum
Detent Quantity:	2
Actuation Method:	Push Button
Grip Length:	1.000 Inches Nominal
Actuation Type:	Push
Shear Strength:	4600 Double Pound
Shoulder To Head End Distance:	1.580 Inches Maximum
Pin Attachment Type:	Link
Detent To Tapered End Distance:	0.380 Inches Maximum
Material:	Aluminum Alloy 380.0 Head And Aluminum Alloy 2011 Head And Aluminum Alloy 2017 Head And Aluminum Alloy 2024 Head And Aluminum Alloy 6061 Head And Aluminum Alloy 7075 Head
Material:	Steel Shank
Material Document And Classification:	Ams-qq-a-225/3 Assn Std 1st Material Response Head And Ams-qq-a-225/5 Assn Std 2nd Material Response Head And Ams-qq-a-225/6 Assn Std 3rd Material Response Head And Ams-qq-a-200/5 Assn Std 4th Material Response Head And Ams-qq-a-225/9 Assn Std 5th Material Response Head
Style Designator:	Button

How to Order

Order this quick release pin from our inventory online by visiting <https://military-fasteners.com/pins/quick+release+pins/NAS1333A3S10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.