

P/N NAS1333C3C15D

Description

NAS1333C3C15D Quick Release Pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1333C3C15D

Minimum Qty (MOQ):

NSN: 5315-01-395-1167

ECCN: EAR99

National Motor Freight: 094380, Cotter Pins / Spring Cotters Iron









^{*} See page 2 for technical characteristics

P/N NAS1333C3C15D Specifications

Head Diameter:	1.200 Inches Nominal
Shank Diameter:	0.1870 Inches Minimum And 0.1895 Inches Maximum
Detent Quantity:	2
Actuation Method:	Push Button
Grip Length:	1.500 Inches Minimum And 1.520 Inches Maximum
Actuation Type:	Push
Shear Strength:	5150 Double Pounds Per Square Inch
Shoulder To Head End Distance:	1.550 Inches Nominal
Pin Attachment Type:	Ring
Detent To Tapered End Distance:	0.380 Inches Nominal
Material:	Steel Comp 302 Head Or Steel Comp 303 Head Or Steel Comp 303se Head Or Steel Comp 316 Head
Material:	Steel Comp 440c Detent
Material:	Steel Comp 630 Shank Or Steel Comp 632 Shank
Material:	Steel Comp 630 Spindle Or Steel Comp 632 Spindle
Material:	Steel Comp 631 Spring
Material Document And Classification:	Ams5643 Assn Std Single Material Response Shank Or Ams5520 Assn Std Single Material Response Shank Or Ams5657 Assn Std Single Material Response Shank
Material Document And Classification:	Ams5643 Assn Std Single Material Response Spindle Or Ams5520 Assn Std Single Material Response Spindle Or Ams5657 Assn Std Single Material Response Spindle
Material Document And Classification:	Mil-s-7720 Mil Spec Single Material Response Head Or Qq-s-763 Mil Spec 1st Material Response Head
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Detent
Material Document And Classification:	Qq-w-423 Fed Spec Single Material Response Spring Or Ams5673 Assn Std Single Material Response Spring
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	Ring Handle
Specification/standard Data:	80205-nas1333 Professional/industrial Association Standard

How to Order

