

**Description**

push type, with hook, NAS1334 series pin

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1334S3S07
Minimum Qty (MOQ):	1
NSN:	5315-00-814-1328
Schedule B:	7318.29.0000
ECCN:	ear99



\* See page 2 for technical characteristics

# P/N NAS1334S3S07 Specifications

Shank Diameter:	0.2470 Inches Minimum And 0.2495 Inches Maximum
Button Handle Diameter:	1.200 Inches Maximum
Actuation Method:	Push Button
Grip Length:	0.700 Inches Minimum And 0.720 Inches Maximum
Actuation Type:	Push
Hardness Rating:	36.0 Rockwell C Minimum Shank And 40.0 Rockwell C Maximum Shank
Hardness Rating:	36.0 Rockwell C Minimum Spindle And 40.0 Rockwell C Maximum Spindle
Hardness Rating:	54.0 Rockwell C Minimum Detent And 64.0 Rockwell C Maximum Detent
Shoulder To Head End Distance:	1.550 Inches Maximum
Pin Attachment Type:	Hook Or Ring
Detent To Tapered End Distance:	0.380 Inches Maximum
Material:	Steel Comp 4130 Shank Or Steel Comp 4135 Shank
Material:	Steel Comp 4130 Spindle
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Shank Or Mil-t-6736 Mil Spec 1st Material Response Shank Or Mil-t-6735 Mil Spec 2nd Material Response Shank
Material Document And Classification:	Mil-s-6758 Mil Spec Single Material Response Spindle
Surface Treatment:	Cadmium Shank And Chromate Shank
Surface Treatment:	Cadmium Spindle And Chromate Spindle
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Shank
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Spindle
Style Designator:	Button
Specification/standard Data:	80205-nas1334 Professional/industrial Association Standard

## How to Order

Order this quick release pin from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1334S3S07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.