

## P/N NAS1351-00-6P

## **Description**

Fastener Length: 3/8", Thread: 0-80, Head Width: 3/64", Thread Length: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1351006P


Minimum Qty (MOQ): 20

NSN: 5305-01-011-3065

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1351-00-6P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.320 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.345 Inches Minimum And 0.375 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.091 Inches Minimum And 0.096 Inches Maximum
Head Height:	0.057 Inches Minimum And 0.060 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.060 Inches
Width Across Flats:	0.050 Inches Minimum And 0.051 Inches Maximum
Thread Quantity Per Inch:	80
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	155000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unrf
Specification/standard Data:	80205-nas1351 Professional/industrial Association Standard

## **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-00-6P">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-00-6P</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.