

## P/N NAS1351-08H2

### **Description**

Fastener Length: 1/8", Hole Diameter: 3/64", Thread: 8-36, Head Width: 9/64", Thread Length: 1/8"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS135108H2

Minimum Qty (MOQ): 1 EA

NSN: 5305-00-902-8441

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1351-08H2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.125 Inches Minimum
Fastener Length:	0.125 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Hole Diameter:	0.047 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.141 Inches Minimum And 0.143 Inches Maximum
Hole Quantity:	6
Hole Type:	Drilled
Thread Quantity Per Inch:	36
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Hole Configuration Style:	Round Internal Hexagon
Material:	Steel Overall
Thread Series Designator:	Unf

## **How to Order**

Order this socket head screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-08H2">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-08H2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.