

P/N NAS1351-08H5P

Description

Fastener Length: 5/16", Hole Diameter: 1/32", Thread: 8-36, Head Width: 9/64", Thread Length: 1/4"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS135108H5P
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-304-2581
Schedule B:	7318.15.2010
FCCN:	9A991



^{*} See page 2 for technical characteristics

P/N NAS1351-08H5P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.242 Inches Minimum And 0.264 Inches Maximum
Fastener Length:	0.298 Inches Minimum And 0.320 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Hole Diameter:	0.044 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.141 Inches Minimum And 0.143 Inches Maximum
Hole Quantity:	6
Hole Type:	Drilled
Thread Quantity Per Inch:	36
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	130000 Pounds Per Square Inch
Hole Configuration Style:	Round
Surface Finish:	125.0 Microinches Overall
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2,cl3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1351 Professional/industrial Association Standard

How to Order

Order this socket head screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-08H5P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.