

P/N NAS1351-3-12

Description

length: 3/4", thread: 10-32, socket head, black oxide finish, alloy steel, NAS1351 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1351312

Minimum Qty (MOQ): 50

NSN: 5305-00-456-9538

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1351-3-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.734 Inches Minimum And 0.766 Inches Maximum
Fastener Length:	0.734 Inches Minimum And 0.766 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.303 Inches Minimum And 0.312 Inches Maximum
Head Height:	0.185 Inches Minimum And 0.190 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.156 Inches Minimum And 0.159 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	130000 Pounds Per Square Inch
Material:	Steel Overall
Thread Series Designator:	Unf

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-3-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.