

**Description**

NAS1351 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1351320
Minimum Qty (MOQ):	25
NSN:	5305-00-182-9355
Schedule B:	7318.15.9000
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



\* See page 2 for technical characteristics

## P/N NAS1351-3-20 Specifications

<b>Thread Class:</b>	3a
<b>Thread Length:</b>	0.875 Inches Minimum
<b>Fastener Length:</b>	1.210 Inches Minimum And 1.250 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.303 Inches Minimum And 0.312 Inches Maximum
<b>Head Height:</b>	0.185 Inches Minimum And 0.190 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Width Across Flats:</b>	0.156 Inches Minimum And 0.159 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Minimum Yield Strength:</b>	130000 Pounds Per Square Inch
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	66 Fed Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unrf
<b>Specification/standard Data:</b>	80205-nas1351 Professional/industrial Association Standard

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-3-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.