

## P/N NAS1351-3-24P

### **Description**

NAS1351 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

MS16998-33

SKU / Model: NAS1351324P

Minimum Qty (MOQ): 25

NSN: 5305-01-111-9419

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1351-3-24P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Minimum
Fastener Length:	1.460 Inches Minimum And 1.500 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.303 Inches Minimum And 0.312 Inches Maximum
Head Height:	0.185 Inches Minimum And 0.190 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.1562 Inches Minimum And 0.1587 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	170000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	150000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrf
Specification/standard Data:	80205-nas1351 Professional/industrial Association Standard

### **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-3-24P">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-3-24P</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.