

Description

NAS1351-3H14 Socet Head Cap Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------------------|
| SKU / Model: | NAS13513H14 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5305-01-493-7016 |
| ECCN: | EAR99 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |



NO IMAGE
AVAILABLE

P/N NAS1351-3H14 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.875 Inches Minimum |
| Fastener Length: | 0.875 Inches Nominal |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.303 Inches Minimum And 0.313 Inches Maximum |
| Head Height: | 0.185 Inches Minimum And 0.190 Inches Maximum |
| Hole Diameter: | 0.045 Inches Minimum And 0.065 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.190 Inches |
| Width Across Flats: | 0.156 Inches Nominal |
| Hole Quantity: | 6 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 32 |
| Hole Configuration Style: | Round |
| Material: | Steel Overall |
| Thread Series Designator: | Unrf |

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-3H14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.