

**Description**

Fastener Length: 1-3/4", Hole Diameter: 3/64", Thread: 10-32, Head Width: 5/32", Thread Length: 7/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS13513H28P
Minimum Qty (MOQ):	10
NSN:	5305-01-024-2425
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS1351-3H28P Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.875 Inches Minimum
<b>Fastener Length:</b>	1.710 Inches Minimum And 1.750 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.303 Inches Minimum And 0.312 Inches Maximum
<b>Head Height:</b>	0.185 Inches Minimum And 0.190 Inches Maximum
<b>Hole Diameter:</b>	0.047 Inches Nominal
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Width Across Flats:</b>	0.156 Inches Minimum And 0.159 Inches Maximum
<b>Hole Quantity:</b>	6
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	180000 Pounds Per Square Inch
<b>Hardness Rating:</b>	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
<b>Minimum Yield Strength:</b>	155000 Pounds Per Square Inch
<b>Hole Configuration Style:</b>	Round Longitudinal Hole
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2 Fed Spec All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unrf
<b>Specification/standard Data:</b>	80205-nas1351 Professional/industrial Association Standard

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-3H28P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.