

**Description**

Fastener Length: 3/8", Hole Diameter: 3/64", Thread: 10-32, Head Width: 5/32", Thread Length: 3/8",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS13513H6P                               |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5305-00-054-2031                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS1351-3H6P Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.283 Inches Minimum And 0.375 Inches Maximum                       |
| <b>Fastener Length:</b>                               | 0.345 Inches Minimum And 0.375 Inches Maximum                       |
| <b>Head Style:</b>                                    | Flat Chamfer  |
| <b>Head Diameter:</b>                                 | 0.303 Inches Minimum And 0.312 Inches Maximum                       |
| <b>Head Height:</b>                                   | 0.185 Inches Minimum And 0.190 Inches Maximum                       |
| <b>Hole Diameter:</b>                                 | 0.044 Inches Minimum And 0.050 Inches Maximum                       |
| <b>Internal Drive Style:</b>                          | Hexagon   |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches  |
| <b>Width Across Flats:</b>                            | 0.156 Inches Minimum And 0.159 Inches Maximum                       |
| <b>Hole Quantity:</b>                                 | 6   |
| <b>Hole Type:</b>                                     | Drilled   |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Minimum Tensile Strength:</b>                      | 180000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>                               | 36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| <b>Minimum Yield Strength:</b>                        | 15000 Pounds Per Square Inch  |
| <b>Hole Configuration Style:</b>                      | Round Internal Hexagon  |
| <b>Material:</b>                                      | Steel Overall   |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall                                |
| <b>Surface Treatment Document And Classification:</b> | Ams-qq-p-416, Ty 2, Cl 2 Fed Spec Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unrf  |
| <b>Specification/standard Data:</b>                   | 80205-nas1351 Professional/industrial Association Standard          |
| <b>Departure From Cited Designator:</b>               | As Mod By Drilled Holes Thru Hd                                     |

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-3H6P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.