

Description

Fastener Length: 25/64", Thread: 10-32, Head Width: 5/32", Thread Length: 25/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS16998-26L](#)

SKU / Model:	NAS13513LL6P
Minimum Qty (MOQ):	10
NSN:	5305-00-492-2207
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1351-3LL6P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.297 Inches Minimum And 0.391 Inches Maximum
Fastener Length:	0.359 Inches Minimum And 0.391 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.185 Inches Minimum And 0.190 Inches Maximum
Head Height:	0.303 Inches Minimum And 0.312 Inches Maximum
Locking Feature:	Strip Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.156 Inches Minimum And 0.159 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	155000 Pounds Per Square Inch
Material:	Plastic Polyamide Locking Feature
Material:	Steel Fastener
Surface Treatment:	Cadmium Fastener And Chromate Fastener
Surface Treatment Document And Classification:	Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unrf
Specification/standard Data:	80205-nas1351 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-3LL6P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.