

P/N NAS1351-4-16

Military-Fasteners.com

Description

Fastener Length: 0-63/64", Thread: 1/4-28, Head Width: 3/16", Thread Length: 0-63/64", NAS1351 series screw

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	NAS1351416
Minimum Qty (MOQ):	25
NSN:	5305-00-477-2714
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1351-4-16 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.913 Inches Minimum And 1.000 Inches Maximum
Fastener Length:	0.970 Inches Minimum And 1.000 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.365 Inches Minimum And 0.375 Inches Maximum
Head Height:	0.244 Inches Minimum And 0.250 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.188 Inches Minimum And 0.190 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	155000 Pounds Per Square Inch
Color:	Black Overall
Material:	Steel Overall
Surface Treatment:	Oxide Overall
Surface Treatment Document And Classification:	Mil-c-13924 Cl1 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unrf
Specification/standard Data:	80205-nas1351 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <u>https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-4-16</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.