

Description

Fastener Length: 1-25/32", Thread: 1/4-28, Head Width: 3/16", Thread Length: 1-"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS13514LL28P |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-901-5074 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1351-4LL28P Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.000 Inches Minimum |
| Fastener Length: | 1.734 Inches Minimum And 1.781 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.365 Inches Minimum And 0.375 Inches Maximum |
| Head Height: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Locking Feature: | Strip Threads |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.250 Inches |
| Width Across Flats: | 0.187 Inches Minimum And 0.190 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 130000 Pounds Per Square Inch |
| Material: | Plastic Polyamide Locking Feature |
| Material: | Steel Fastener |
| Surface Treatment: | Cadmium Fastener And Chromate Fastener |
| Surface Treatment Document And Classification: | Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Fastener |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas1351 Professional/industrial Association Standard |

How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-4LL28P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.