

P/N NAS1351-5-48P

Description

Fastener Length: 2-63/64", Thread: 1/4-24, Thread Length: 2-63/64", NAS1351 series screw

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | NAS1351548P |
|-------------------------|---|
| Minimum Qty (MOQ): | 5 |
| NSN: | 5305-01-304-5769 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



^{*} See page 2 for technical characteristics

P/N NAS1351-5-48P Specifications

| Thread Class: | 3a |
|------------------------------|---|
| Thread Direction: | Right-hand |
| Thread Length: | 2.857 Inches Minimum And 3.000 Inches Maximum |
| Fastener Length: | 2.940 Inches Minimum And 3.000 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.457 Inches Minimum And 0.469 Inches Maximum |
| Head Height: | 0.308 Inches Minimum And 0.317 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 180000 Pounds Per Square Inch |
| Hardness Rating: | 39.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas1351 Professional/industrial Association Standard |

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-5-48P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.