

# P/N NAS1351-5-48P

## **Description**

Fastener Length: 2-63/64", Thread: 1/4-24, Thread Length: 2-63/64", NAS1351 series screw

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS1351548P
Minimum Qty (MOQ):	5
NSN:	5305-01-304-5769
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1351-5-48P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	2.857 Inches Minimum And 3.000 Inches Maximum
Fastener Length:	2.940 Inches Minimum And 3.000 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.457 Inches Minimum And 0.469 Inches Maximum
Head Height:	0.308 Inches Minimum And 0.317 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1351 Professional/industrial Association Standard

### **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-5-48P">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-5-48P</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.