

**Description**

Fastener Length: 63/64", Hole Diameter: 3/64", Thread: 1/4-24, Head Width: 1/4", Thread Length: 0-63/64",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS13515H16P
Minimum Qty (MOQ):	10
NSN:	5305-00-099-7877
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS1351-5H16P Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.887 Inches Minimum And 1.000 Inches Maximum
<b>Fastener Length:</b>	0.970 Inches Minimum And 1.000 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.457 Inches Minimum And 0.469 Inches Maximum
<b>Head Height:</b>	0.306 Inches Minimum And 0.312 Inches Maximum
<b>Hole Diameter:</b>	0.044 Inches Minimum And 0.050 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Width Across Flats:</b>	0.250 Inches Minimum And 0.253 Inches Maximum
<b>Hole Quantity:</b>	1
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Hardness Rating:</b>	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
<b>Minimum Yield Strength:</b>	30000 Pounds Per Square Inch
<b>Hole Configuration Style:</b>	Round Internal Hexagon
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 T31 Cl2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unrf
<b>Specification/standard Data:</b>	80205-nas1351 Professional/industrial Association Standard

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-5H16P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.