



Military-Fasteners.com

P/N NAS1351-5H36P

Description

Fastener Length: 2-1/4", Hole Diameter: 3/64", Thread: 5/16-24, Head Width: 1/4", Thread Length: 1-1/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS13515H36P
Minimum Qty (MOQ):	1
NSN:	5305-01-579-7146
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N NAS1351-5H36P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.125 Inches Minimum
Fastener Length:	2.250 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.457 Inches Minimum And 0.469 Inches Maximum
Head Height:	0.306 Inches Minimum And 0.312 Inches Maximum
Hole Diameter:	0.044 Inches Minimum And 0.050 Inches Maximum
Internal Drive Style:	Hexagon
End Item Identification:	3mh60sc Airframe; Guide Assembly
Nominal Thread Diameter:	0.313 Inches
Width Across Flats:	0.250 Inches Nominal
Hole Quantity:	6
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Yield Strength:	10400 Pounds Per Square Inch
Hole Configuration Style:	Round Internal Hexagon
Part Name Assigned By Controlling Agency:	Inavy: Screw,cap,socket,he; Std: Screw, Cap, Socket Head, Drilled, Plain, Alloy Steel, Unrf-3a
Color:	Black Overall
Material:	Steel Overall
Material Document And Classification:	Ff-s-86 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams-qq-p-416, Type II, Class 2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unrf
Fsc Application Data:	Unrf

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-5H36P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.