

**Description**

Fastener Length: 63/64", Thread: 3/8-24, Head Width: 5/16", Thread Length: 63/64", NAS1351 series screw


\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS16998-74](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1351616P                               |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5305-00-235-1669                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS1351-6-16P Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.901 Inches Minimum And 1.016 Inches Maximum                       |
| <b>Fastener Length:</b>                               | 0.984 Inches Minimum And 1.016 Inches Maximum                       |
| <b>Head Style:</b>                                    | Flat Chamfer  |
| <b>Head Diameter:</b>                                 | 0.550 Inches Minimum And 0.562 Inches Maximum                       |
| <b>Head Height:</b>                                   | 0.368 Inches Minimum And 0.375 Inches Maximum                       |
| <b>Internal Drive Style:</b>                          | Hexagon   |
| <b>Nominal Thread Diameter:</b>                       | 0.375 Inches  |
| <b>Width Across Flats:</b>                            | 0.312 Inches Minimum And 0.316 Inches Maximum                       |
| <b>Thread Quantity Per Inch:</b>                      | 24  |
| <b>Minimum Tensile Strength:</b>                      | 170000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>                               | 38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| <b>Minimum Yield Strength:</b>                        | 150000 Pounds Per Square Inch                                       |
| <b>Material:</b>                                      | Steel Overall   |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall                                |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall         |
| <b>Thread Series Designator:</b>                      | Unrf  |
| <b>Specification/standard Data:</b>                   | 80205-nas1351 Professional/Industrial Association Standard          |

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-6-16P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.