

Description

Fastener Length: 63/64", Thread: 3/8-24, Head Width: 5/16", Thread Length: 63/64", NAS1351 series screw


* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS16998-74](#)

SKU / Model:	NAS1351616P
Minimum Qty (MOQ):	5
NSN:	5305-00-235-1669
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1351-6-16P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.901 Inches Minimum And 1.016 Inches Maximum
Fastener Length:	0.984 Inches Minimum And 1.016 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.550 Inches Minimum And 0.562 Inches Maximum
Head Height:	0.368 Inches Minimum And 0.375 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.375 Inches
Width Across Flats:	0.312 Inches Minimum And 0.316 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	170000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	150000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unrf
Specification/standard Data:	80205-nas1351 Professional/Industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1351-6-16P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.